


The diagram shows a cross-section of a door threshold. A dashed rectangle represents the door jamb. Inside, a ramp is shown with a hatched pattern, sloping from the exterior level down to the interior floor level. Labels include: "Door Jamb" at the top, "EXTERIOR" on the left, "INTERIOR" on the right, "Max. 1:8 gradient to ramp" with an arrow pointing to the ramp, "Entry level landing 1:40 fall" with an arrow pointing to the exterior level, "FFL" (Finished Floor Level) on the interior side, and "Threshold ramp Confined within depth of door jamb" at the bottom right. A small circle with a crosshair is shown on the exterior level line.

ALL SMOKE ALARMS TO BE HARDWIRED &
INTERCONNECTED.
SMOKE ALARMS TO BE PHOTOELECTRIC TYPE IN
ACCORDANCE WITH NCC 2022 PART 9.5 & AS 3786



The fall of the floor surface to a floor waste must be-

- a- between 1:60 and 1:80 in the shower area
- b- between 1:80 and 1:100 in other areas

LIVING	=	136.8 m ²
GARAGE	=	29.2 m ²
PORCH	=	1.6 m ²
PATIO	=	13.0 m ²
TOTAL	=	180.6 m ²

FLOOR PLAN

Preliminay Plans 4/10/2024